

FOR AUTHORIZED USE ONLY

SHRI GURU GOBIND SINGHJI INSTITUTE OF ENGINEERING & TECHNOLOGY,

VISHNUPURI, NANDED - 431 606

Quotation Notice & Quotation

For

"Providing and fixing rolling shutter to sub-station"



SHRI GURU GOBIND SINGHJI INSTITUTE OF ENGINEERING & TECHNOLOGY, VISHNUPURI, NANDED-431 606.

Date: 15/06/2022

SHORT NOTICE FOR CONTRACTORS

Sealed quotations are invited for <u>Providing and fixing rolling shutter to sub-station</u>. The prescribed format of this work is available our institute web site https://sggs.ac.in/tenders-site-section/, from 17/06/2022 to 24/06/2022. The interested Govt. registered civil contractors/Agencies are requested to give their quotations for above mentioned work up to 24/06/2022. before 01.30 p.m. If possible, the quotations will be opened at 3.00 p.m. on the same day or next working day in the presence of contractor who will be remaining present.

The rights are reserved to accept or reject any or all quotation without any notice.

The contractors/Agencies should attach the following documents with Quotation:-

- 1. The contractor should attach with quotation the Registration copy of contractor with any of these Government Department PWD, CPWD, BSNL, MJP, MSSIDC and DIC.
- 2. Certificate of GST No.

In the absence of above any documents quotation stand cancelled.

Site Engineer

Copy to the:

Building & Constructions Committee S.G.G.S. Institute of Engg. & Tech.

Vishnupuri, Nanded

- 01 All Notice Boards in this Institute.
- 02 Concerned file No. 10
- 03 Institute web site.

Name of Contractor:	



SHRI GURU GOBIND SINGHJI INSTITUTE OF ENGINEERING & TECHNOLOGY, VISHNUPURI, NANDED-431 606.

QUOTATION

Name of the Work :- Providing and fixing rolling shutter to sub-station.

Name of work		Unit	Rate per Unit	Total Amount
Item No.1: Providing and fixing rolling shutter fabricated from steel laths of minimum thickness 0.9 mm with lock plate of 3.15 mm thickness reinforced with 35x35x5mm angle section fitted with sliding bolts and handles for both sides, deep M.S. channel section of depth and thickness not less than 65 mm and 3.15 mm respectively with hold fast arrangements, M.S. Bracket plate 300x300x3.15 mm minimum size and shape with square bar, suspension shaft of minimum 32 mm diameter, hood cover of M.S. sheet not less than 0.9 mm thickness and of any size at top and safety devices including mechanical gear operation arrangement consisting of worm gearwheels and worms of high grade cast iron or mild steel and one coat of red load primer etc complete.(I.S.62481979) (Without mechanical gear)	9.30	Sq.M.		
	Total An	nount :-		

(Rate should be inclusive of GST)*	
(Inwards)
Place :-	
Date :-	